







































- Yang, E. and Li, V.C. (2010), "Strain-hardening fiber cement optimization and component tailoring by means of a micromechanical model". *Constr. Build. Mater.*, **24**, 130-139.  
<https://doi.org/10.1016/j.conbuildmat.2007.05.014>
- Yang, E., Wang, S., Yang, Y. and Li, V.C. (2008), "Fiber-bridging constitutive law of engineered cementitious composites", *Adv. Concrete Tech.*, **6**, 181-193. <https://doi.org/10.3151/jact.6.181>
- Yang, E.H., Sahmaran, M., Yang, Y. and Li, V.C. (2009), "Rheological control in production of engineered cementitious composites", *ACI Mater.*, **106**(4), 357-366.
- Yu, J., Weng, W. and Yu, K. (2014), "Effect of different cooling regimes on the mechanical properties of cementitious composites subjected to high temperatures", *Sci. World J.*  
<http://dx.doi.org/10.1155/2014/289213>
- Yu, J., Lin, J., Zhang, Z. and Li, V.C. (2015), "Mechanical performance of ECC with high-volume fly ash after sub-elevated temperatures", *Constr. Build. Mater.*, **99**, 82-89.  
<https://doi.org/10.1016/j.conbuildmat.2015.09.002>
- Yu, K.Q., Yu, J.T., Dai, J.G., Lu, Z.D. and Shah, S.P. (2018), "Development of ultra-high performance engineered cementitious composites using polyethylene (PE) fibers", *Constr. Build. Mater.*, **158**, 217-227.  
<https://doi.org/10.1016/j.conbuildmat.2017.10.040>
- Zhang, J., Wang, Z., Ju, X. and Shi, Z. (2014), "Simulation of flexural performance of layered ECC-concrete composite beam with fracture mechanics model", *Eng. Fract. Mech.*, **131**, 419-438.  
<https://doi.org/10.1016/j.engfracmech.2014.08.016>