























- Latthe, S.S., Kodag, V.S., Sutar, R.S., Bhosale, A.K., Nagappan, S., Ha, C.S., Sadasivuni, K.K., Kulal, S.R., Liu, S. and Xing, R. (2020), "Sawdust-based superhydrophobic pellets for efficient oil-water separation", *Mater. Chem. Phys.*, **243**, 1-10. <https://doi.org/10.1016/j.matchemphys.2020.122634>
- Li, T.Q. and Wolcott, M.P. (2006), "Rheology of wood plastics melt. Part 2. Effects of lubricating systems in HDPE/maple composites", *Polym. Eng. Sci.*, **46**(4), 464-473. <https://doi.org/10.1002/pen.20505>
- Moslemi, A. (1988), "Inorganically bonded wood composites", *Chem. Tech.*, **18**(8), 504-510.
- Nannan, L., Hongqiang, Y., Lei, X., Lebo, M., Zhengping, F., Yihu, S. and Hao, W. (2015), "Flame retarding and reinforcing modification of ramie/ polybenzoxazine composites by surface treatment of ramie fabric", *Compos. Sci. Technol.*, **121**, 82-88. <https://doi.org/10.1016/j.compscitech.2015.07.013>
- Ohashi, S. and Ishida, H. (2017), *Advanced and Emerging Polybenzoxazine Science and Technology*, Elsevier, USA.
- Radoslaw, M., Dorota, D., Adam, D., Rafal, C. and Dorota, D. (2020), "By-Products of sawmill industry as raw materials for manufacture of chip-sawdust boards", *J. Build. Eng.*, **32**(1), 1-26. <https://doi.org/10.1016/j.jobbe.2020.101460>
- Ravi, M.R., Jhalani, A. Sinha, S. and Anjan, R. (2004), "Development of a semi-empirical model for pyrolysis of an annular sawdust bed", *J. Anal. Appl. Pyrol.*, **71**(1), 353-374. [https://doi.org/10.1016/S0165-2370\(03\)00102-5](https://doi.org/10.1016/S0165-2370(03)00102-5)
- Ribeiro, A.B., Mateus, E.P., Ottosen, L.M. and Nielsen, G.B. (2000), "Electrodialytic removal of Cu, Cr, and As from chromated copper arsenate-treated timber waste", *Environ. Sci. Technol.*, **34**(5), 784-788. <https://doi.org/10.1021/es990442e>
- Rimduisit, S., Tanthapanichakoon, W. and Jubsilp, C. (2006), "High performance wood composites from highly filled polybenzoxazine", *J. Appl. Polym. Sci.*, **99**(3), 1240-1253. <https://doi.org/10.1002/app.22607>
- Rimduisit, S., Kampangsaeree, N., Tanthapanichakoon, W., Takeichi, T. and Suppakarn, N. (2007), "Development of wood-substituted composites from highly filled polybenzoxazine-phenolic novolac alloys", *Polym. Eng. Sci.*, **47**(2), 140-149. <https://doi.org/10.1002/pen.20683>
- Rimduisit, S., Jubsilp, C. and Tiptipakoran, S. (2013), *Alloys and Composites of Polybenzoxazines*, Springer, Singapore.
- Tiuc, A.E., Nemeş, O., Vermeşan, H. and Toma, A.C. (2019), "New sound absorbent composite materials based on sawdust and polyurethane foam", *Compos. B. Eng.*, **165**, 120-130. <https://doi.org/10.1016/j.compositesb.2018.11.103>
- Yagci, Y., Kiskan, B. and Ghosh, N.N. (2009), "Recent advancement on polybenzoxazine-a newly developed high performance thermoset", *J. Polym. Sci. Part A: Polym. Chem.*, **47**(21), 5565-5576. <https://doi.org/10.1002/pola.23597>
- Yousefi, A. and Lafleur, P.G. (1997), "Kinetic studies of thermoset cure reactions: a review", *Polym. Compos.*, **18**(2), 157-168. <https://doi.org/10.1002/pc.10270>
- Zafeiropoulos, N.E., Baillie, C.A. and Hodgkinson, J.M. (2002), "Engineering and characterization of the interface in flax fibre/polypropylene composite materials. Part II. The effect of surface treatments on the interface", *Composites Part A*, **33**(9), 1185-1190. [https://doi.org/10.1016/S1359-835X\(02\)00088-X](https://doi.org/10.1016/S1359-835X(02)00088-X)